

Capable of  
recording  
hundreds of  
millions of  
records at up to  
64 Hz

## Lowell Instruments MAT-1 Data Logger

### Magnetometer - Accelerometer - Thermistor

The Lowell Instruments MAT-1 Data Logger contains an integrated 3-axis magnetometer, 3-axis accelerometer and a precision temperature sensor. The logger includes a microSD flash memory card, a long-life lithium battery, an O-ring sealed waterproof housing and a USB communication interface. The logger is capable of recording hundreds of millions of magnetometer and accelerometer records at up to 64 Hz as well as temperature records at 1 Hz.



Feature	Benefit
<b>3-axis Accelerometer</b>	Resolve static orientation to 1° Record dynamic acceleration at 64 Hz
<b>3-axis Magnetometer</b>	+/- 5° nominal compass bearing accuracy Temperature compensated
<b>Precision Temperature</b>	Accurate to +/-0.1 °C from -5 to 30 °C Accurate to +/-0.2 °C from -20 to -5, 30 to 50 °C
<b>Large Memory</b>	8 GB microSD flash card, upgradable to 32 GB
<b>Long Battery Life</b>	Hundreds of millions of records over a year+
<b>Rugged Housing</b>	O-ring sealed PVC or Titanium housing
<b>USB 2.0 Interface</b>	Connect with standard USB cables

The MAT-1 is ideal for determining the static orientation of vehicles, packages and assets. The MAT-1 can also be used for vibration analysis and motion studies. The internal thermistor provides a detailed record of temperature in the target environment. The logger's large memory, high recording rate, long battery life and rugged design make it suitable for a wide range of applications.

#### Applications

- |                                    |                              |
|------------------------------------|------------------------------|
| • Oceanographic Tilt Current Meter | • Animal Tagging             |
| • Underwater Vehicle Heading       | • Vehicle Dynamics           |
| • Equipment Monitoring             | • Shipping Monitoring        |
| • Vibration Analysis               | • Mooring Orientation & Tilt |

The MAT-1 Data Logger includes Windows® software to configure the logger for deployment. After the deployment is complete, the data file is transferred from the memory card via USB cable or SD card reader and the data are post-processed for filtering, plotting and analysis.

## Specifications

	Magnetometer	Accelerometer	Thermistor
Type	3-axis magnetoresistive sensor with 12-bit A/D Converter	3-axis MEMS Accelerometer with 12-bit A/D Converter	NTC Thermistor with 16-bit A/D Converter
Filtering	None	1600 Hz averaging: up to 32 values per measurement	Hardware: low-pass filter
Range	+/- 1.2 Gauss standard Custom range on request	+/- 2 g standard +/- 4 g optional	-20 to 50 °C
Accuracy	+/- 5° compass bearing typical	0.01 g	+/-0.1 °C (-5 to 30 °C) +/-0.2 °C (-20 to -5, 30 to 50°C)
Resolution	<0.001 Gauss	<0.001 g	<0.01 °C
Maximum Rate	64 Hz	64 Hz	1 Hz

### Environmental

Operating Temperature	-20 to 50 °C	
Depth Rating	PVC: 300 m	Titanium: 4500 m

### Electronics

Memory	8 GB microSDHC flash card (upgradable to 32GB)
Communications	Full speed USB micro-B port
Battery Type	3.6 V, size "A", user replaceable lithium (from Lowell Instruments)
Battery Life	Months to years depending on operating mode
Internal Clock	1 minute per month

### Operating Modes

Recording Rates	Accelerometer and Magnetometer to 64 Hz Temperature to 1 Hz
Start and Stop	Start and Stop at user defined times
Burst Mode	Variable rate logging at user defined interval

### Mechanical

Dimensions	PVC: 27 mm (1.05") diameter x 213 mm (8.39") length	Titanium: 25.4 mm (1.00") diameter x 223 mm (8.78") length
Weight	PVC: 143 g (5.1 oz)	Titanium: 225g (8.39 oz)
Construction	Housing: Grey PVC or Titanium O-ring: EPDM (PVC) Buna (Titanium)	

### Other

Software	Free Windows® Compatible Software
USB	USB 2.0 compliant MSC and CDC Classes
Firmware	Field upgradable via USB cable

