

EnviroMonitors Ford Lane Business Park Ford West Sussex BN18 OUZ, UK www.enviromonitors.co.u



DISCONTINUED: FieldScout pH 600 Meter

Product Images







Short Description

- The new FieldScout pH 400 Meter has a modern, intuitive, and user friendly interface that allows users to quickly access the meters advanced features and settings
- Temperature and pH data remain visible, so monitoring does not stop when settings are changed or options are selected
- Large, backlit 3.2" LCD color display ensures measurement values and menu options are easy to read.

Description

A quality pH meter using ISFET probes for glass-free pH measurement!

Well suited for the research community, education, agriculture, horticulture, bioscience, turf, and more!

Note: The FieldScout pH 600 Meter does not include a pH probe: please select from pH probe options above.

Modern User Interface

- The new FieldScout pH 600 Meter has a modern, intuitive, and user friendly interface that allows users to quickly access the meters advanced features and settings
- Temperature and pH data remain visible, so monitoring does not stop when settings are changed or options are selected
- Large, backlit 3.2" LCD color display ensures measurement values and menu options are easy to read

Rugged and Ergonomic Design

- The FieldScout pH 600 Meter has been designed for professional use
- Protected against dust and splashing IP65
- Meters are fitted with a rubber boot to help absorb shock
- The USB port is well protected by a tightly sealed cover. The casing and battery door are fitted with rubber seals.
- 1 year warranty.

Additional Information

Country of Manufacture	United States	United States	
Promotion	This product has been discontinued. Se	This product has been discontinued. See our full range of pH Meters	
Brand	Spectrum Technologies	Spectrum Technologies	
	 Professional grade quality Large, 3.2" LCD color display allows easy Intelligent calibration wizard simplifies the Light weight and compact design make it handheld applications Powered by 3 rechargeable AA-batteries Resolution - 0.005 Internal storage of measured data points Stored and logged data points can be trate (65,000 max.) Ability to query both momentary pH value Supports up to 5-point calibration Alarm set points and warnings for pH and the momentary pH value Meter includes case with cavity for senso Excludes pH probe, please order separate ISFET (Ion Sensitive Field Effect Transist Glass Free and Durable Probe - 2 Options Unlike glass electrodes, the FieldScout 40 electrodes that will not shatter. Additiona Both come with a 6-month warranty Spectrum ISFET probes are made of high PVC Sample directly in plug trays, pots, contain 	thighly suitable for field use and (AC adapter included) (ac (AC adapter included) (ac (AC adapter included) (ac (AC adapter included) (b) (c) (c) (c) (c) (c) (c) (c	
	media		
	SPECIFICATIONS	pH 400 Meter pH	
	pH Accuracy*	± 0.01	
	Resolution*	0.01	
	Range* Calibration	pH 0.00 to 14.00 Smart calibration wizard	
	1-Point	✓	
xplanation	2-Point 3-Point	~	
	5-Point		
	Buffer types Spectrum	,	
	DIN, NIST, JIS		
	Automatic Temperature Correction (ATC)	✓	
	Temperature		
	Accuracy*	± 0.5°C (0.9°F)	
	Resolution* Range*	0.1°C (0.1°F) -5 to 120°C (20 to 250°F)	
	Options		
	Languages	English, Dutch, French, German,	
	Bias setting (user definable fixed offset value) Data handling	pH 0.00 to 9.99	
	Store current measurement value(s) manually	max. 10	
	Log measurement value(s) automatically at user defi	inable interval 1-60 sec.	
	Send logged data file to PC through USB Remote readout from PC through USB (max. 1 read	lout per sec.)	
	Send calibration report(s) to PC through USB		
	Alarm setpoints and warnings (user definable min-max	settings)	
	Temperature		
	Stability check (change in pH per unit time)		
	Physical Properties		
	Dimensions (W x H x D) Weight	3.13" x 6.30" x 1.14" (80mm x 160n 13.4 oz (379 gram)	
	Operation	8h continuous / 30h with power sav	
	Protection rating Batteries	IP65 (splash water resistar 3 x AA NIMH 2600mAh	
	Replaceable	✓	
	Rechargeable via USB (5VDC - minimum 500mA to Recharge time (empty-full, with Spectrum charger, @		
	* Depends on probe being used		
	Meter includes case with cavity for sensor,	hatteries and pH 4 and 7 standards	
Contents	Excludes pH probes, please order separati Blunt Tip SI-2127 Pin Point Tip SI-2128		
deal For	Professional, Education, Agronomy	Professional, Education, Agronomy	

Additional Options

pH Probe Options	pH Meter Blunt Tip ISFET Probe
	pH Meter Pin Point Tip ISFET Probe