

EnviroMonitors Ford Lane Business Park Ford West Sussex BN18 OUZ, UK www.enviromonitors.co.u



HOBO S-LWA-M003 Leaf Wetness Smart Sensor

Product Images







Description

The Leaf Wetness Smart Sensor provides accurate leaf wetness data in a number of growing and research applications. The sensor is ready to use and does not require any painting or coating. It uses a capacitive grid that is less sensitive to surface residues than resistive grid-based sensors, and comes preconditioned for consistent measurements between sensors and for long-term stability.

Along with a 3-metre cable, a mounting bracket is included so the sensor can be easily positioned to mimic the wet-dry characteristics of the plants being studied.

Features

- Preconditioned for consistent measurements
- Does not require any painting or coating

| 3-metre cable and mounting bracket included. | | |
|--|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

Additional Information

| Country of Manufacture | United States |
|------------------------|--|
| | The country of origin for this product is the United States. To see the full specifications for this product, please see the manual found under the Resources tab. Measurement range: 0 (dry) to 100% (wet) Operating range: -40°C to 70°C, (-40°F to 158°F) Repeatability: ± 5% Resolution: 0.59% Stability: < ± 5% per year Interchangeability between sensors (over the range 10-90%): ± 10% Measurement averaging option: No Housing: No coating required Sensor type: Capacitive Grid |
| Explanation | <u>Dimensions</u> Sensor plate: 4.7 cm x 5.1 cm (1.8" x 2.0") Tube: 12.2 cm length x 1.8 cm diameter (4.8" x 0.7") |
| | Cable length: 3m (9.8') Length of Smart Sensor Network Cable: 3m Approximate weight: 127 g (4.5 oz) for sensor, and 290 g (10.2 oz) with mounting bracket Mounting bracket: 20 cm long (8"); Sensor can be positioned at any angle between 0 and 90 degrees (vertical) Number of data channels: 1 For mounting on tripods or masts 3.2 cm to 4.1 cm (1 1/4" to 1 5/8"), Cross Arms (Part # M-CAA or M-CAB), or flat surfaces. U-bolt and tie-wraps included. |
| | The CE Marking identifies this product as complying with all relevant directives in the European Union (EU) |
| Contents | HOBO S-LWA-M003 Leaf Wetness Smart Sensor Mounting bracket U-bolt Tie wraps |
| Ideal For | Professional, Agronomy |
| Brand | Onset HOBO |
| Housing | Cable |
| Measurements | Leaf Wetness |
| Compatible With | RX3000 Remote Monitoring Station Data Logger, RX2100 MicroRX Station, RX2100-WL MicroRX Water Level Station, U30-NRC U30 USB Weather Station Data Logger, H21-USB USB Micro Station Data Logger |
| | |