



HOBO MX2304 Wireless Temperature Data Logger with External Sensor - Optional Remote Monitoring

Product Images



Short Description


The HOBO MX2304 is a weatherproof indoor/outdoor data logger with one external temperature sensor. Leveraging Bluetooth Low Energy, the logger enables easy, fast set up and data download directly from your mobile device. For remote cloud-based access to your data and alerts, simply add the optional [MX Gateway](#).

Description

Key Features

- Convenient wireless setup and data download via Bluetooth Low Energy, or via the cloud with the optional MX Gateway
- View current data in real time with the free HOBOnnect app, and near real-time cloud-based monitoring with the optional MX Gateway
- Receive alert notifications for out-of-range conditions via email or SMS text message with the optional MX Gateway
- Visual alerts on the data logger and app
- Retrieve data in hard-to-reach locations
- Compact, weatherproof housing with built-in mounting system
- Share downloaded data easily from your mobile device
- Accuracy: +/- 0.2C°.

Additional Information

Country of Manufacture	United States
Brand	Onset HOBO
Measurements	Temperature
Typical applications	Environmental (Indoor), Environmental (Outdoor), Field Research, Food Safety
Onset Product Series	MX2300
Explanation	<p>Features:</p> <ul style="list-style-type: none">• Convenient wireless setup and download via Bluetooth Low Energy (100-foot range)• Retrieve data in hard-to-reach locations• Visual alarms alert you to out-of-range conditions• Compact, weatherproof housing with built-in mounting• View current data in real time with Onset's free HOBOMobile app• Share downloaded data easily from your mobile device• Accuracy: +/- 0.2C° <p>Download the HOBOMobile app:</p> 
Contents	<ul style="list-style-type: none">• HOBO MX2304 1 Ext Temp Data Logger• Screws• Cable ties
Ideal For	Professional, Agronomy
Power	Battery only

Temperature Sensor:

Sensors	Range	MX2301 and MX2305 internal sensors: -40 to 70°C (-40 to 158°F) MX2302 external temperature sensor: -40 to 70°C (-40 to 158°F) MX2303 and MX2304 external sensors: -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year
	Accuracy	±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 0 to 70°C (±0.36 from 32 to 158°F) ±0.25°C from 70 to 100°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only
	Resolution	0.04°C (0.072°F)
	Drift	<0.01°C (0.018°F) per year
	Batteries	2/3 AA 3.6 Volt lithium, user replaceable

Additional Options

Optional Remote Cloud Access to Your Data

MX Gateway for HOBO MX Data Loggers (SKU: MXGTW1)

HOBOLink Service Plan (One Year Subscription (SKU: SP-620)) - one
required per MX Gateway

Temperature Calibration Certificate

2 Point Temperature Calibration (0°C / 60°C)

2 Point Temperature Calibration (please specify temperature points)

1 Point Temperature Calibration (0°C)