

EnviroMonitors
Ford Lane Business Park
Ford
West Sussex
BN18 0UZ, UK
www.enviromonitors.co.u



Spectrum FieldScout TDR 250 Economy Soil Moisture Meter

Product Images







Short Description

The TDR 250 is a simplified portable soil moisture meter that captures measurements in the root zone.

- Capture soil moisture measurements in the root zone
- Maintain consistent turf quality
- Conserve water and reduce labour costs.

The TDR 250 offers the same proven time-domain measurement technology as the TDR 350, but at less investment.

Description

TDR Soil Moisture Meters are the industry standard for site-specific soil moisture measurements.

Applications

- Irrigation scheduling, syringing practices, and soil flushes
- Ideal for golf courses, sports turf fields, and raw crop farmers.

Features

- Displays VWC% (soil moisture, with running average)
- Soil measurements in less than a second
- Operates in TDR 300 mode or salinity-corrected (TDR 350) mode
- Settings for standard, high-clay, or sand soil type
- Internal data logging up to 124,000 measurements
- USB port for USB drive data download
- High-contrast display with backlight for easy viewing
- Ergonomic, portable design with removable handles
- Interchangeable soil probes sold separately.

Note: Rods are required for the TDR250 to function.

Want Some Helpful Advice?

Call 01243 558280, click on the webchat box below, or fill out our contact form.

Additional Information

Country of Manufacture	United States
Brand	Spectrum Technologies
Explanation	Display: An industry exclusive, larger backlit LCD display provides optimal contrasts for daylight and low light viewing, and larger digits for easier viewing of measurements. Receive instant readings – no smartphone or computer hookup required! Data logging: Large capacity data logger can record approximately Data records can be saved to USB drive. Design: The TDR 250 has an ergonomic design with a shaft-mounted probe. This allows users to easily and rapidly take many measurements in various turf and soil environments. Measurement Principle: Time-domain Measurement Units: Percent Soil Volumetric Water Content (VWC) Resolution: 0.1%. VWC Accuracy: +- 3.0% VWC Data Logger: Up to 124,000 measurements Range: 0% to saturation (Saturation up to 50% depending on soil type).
Contents	Rods Sold Separately
Ideal For	Professional, Agronomy
Power	Battery only
Power	Battery only (4 x AA included)
Typical applications	Environmental (Outdoor), Field Research
Measurements	Soil Electrical Conductivity (EC), Soil Moisture, Soil Temperature